

TYRES

Product group	Tyres
Item number	10001414
Valid tyre size	520 / 85 R 42
LI / SI / PR	157 D / 154 E
TL/TT	TL
Brand	Firestone
Tread pattern	Performer 85
Sonderpostenkategorie	Damaged
type of damage	Dismounted,Stud damage



Notes and features

- Narrow tyre for maintenance of row crops.
- High load capacity.
- Outstanding driving dynamics on the road.
- Very good traction and self-cleaning.
- Long service life.



Technical Informations

Item number	10001414
EAN	4040658112003
Valid tyre size	520 / 85 R 42
LI / SI / PR	157 D / 154 E
TL/TT	TL
Brand	Firestone
Tread pattern	Performer 85
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	240,40
Recommended rim size	18
Permitted rim size	16
Maximum air pressure [bar].	1,60
Section width (mm)	561
Outer diameter of tyre [mm].	1946
Stat. radius (SLR) [mm]	876
Rolling circumference [mm].	5838
Tread depth (mm)	55,0
Number of lugs	22x2
Tyre capacity 75% [ltr.]	570
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
157 D	4125	65		1,60	
154 E	3750	70		1,60	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.