Bohnenkamp Moving Professionals

TYRES

Product group	Tyres
Item number	10001440
Valid tyre size	650 / 75 R 38
LI / SI / PR	169 D / 165 E
TL/TT	TL
Brand	Michelin
Tread pattern	MachXBib
Sonderpostenkategorie	Damaged
type of damage	Dismounted,Scratcher in the flank





Notes and features

- Super-wide tyre for upper performance class.
- Specially designed for gentle soil tillage.

• Suitable for heavy road transport.

Bohnenkamp Moving Professionals

Technical Informations

Item number	10001440
EAN	4040658112232
Valid tyre size	650 / 75 R 38
	000775 K 30
LI / SI / PR	169 D / 165 E
TL/TT	ть
Brand	Michelin
Tread pattern	MachXBib
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	325,00
Recommended rim size	DW23B
Permitted rim size	MW23B
Maximum air pressure [bar].	2,40
Section width (mm)	709
Outer diameter of tyre [mm].	1948
Stat. radius (SLR) [mm]	871
Rolling circumference [mm].	5786
Tread depth (mm)	66,0
Tyre capacity 75% [ltr.]	731
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
169 D	5800	65		2,40	
165 E	5150	70		2,40	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.