

## RIMS

|                  |           |
|------------------|-----------|
| Product group    | Rims      |
| Item number      | 10001474  |
| Valid rim size   | 9 x 18    |
| Rim connection   | 8/221/275 |
| Bolt hole design | B3        |
| Offset (mm)      | +17       |
| Rim colour       | Silver    |
| Brand            | Jantsa    |



## Technical Informations

|                             |            |
|-----------------------------|------------|
| Load capacity of rim 1 [kg] | 4000       |
| Speed Rims 1 [km/h]         | 20         |
| Load capacity of rim 2 [kg] | 3200       |
| Speed Rims 2 [km/h]         | 40         |
| Load capacity of rim 3 [kg] | 4400       |
| Speed Rims 3 [km/h]         | 10         |
| Load capacity of rim 4 [kg] | 3550       |
| Speed of wheels 4 [km/h].   | 30         |
| Maximum speed [km/h].       | 40         |
| Type of drive               | Towed axle |
| Nettogewicht [kg] (gültig)  | 25,00      |

|                                       |                  |
|---------------------------------------|------------------|
| <b>Hump</b>                           | kein Hump        |
| <b>Valve protection</b>               | VSH              |
| <b>Single / multi-part</b>            | einteilig        |
| <b>Rim material</b>                   | steel            |
| <b>RAL</b>                            | RAL9006          |
| <b>Cavity Sealed</b>                  | No               |
| <b>Disc thickness [mm]</b>            | 10               |
| <b>Knurling</b>                       | without knurling |
| <b>Verschweißung beidseitig</b>       | No               |
| <b>Ventilation holes</b>              | No               |
| <b>Rim centering</b>                  | BC               |
| <b>Number of bolt holes</b>           | 8                |
| <b>Bolt hole design EUWA</b>          | B22 DS 36        |
| <b>Bolt hole diameter [mm]</b>        | 27               |
| <b>Countersinking</b>                 | Sphere           |
| <b>Spherical countersink [mm].</b>    | R18              |
| <b>hub hole diameter [mm].</b>        | 221              |
| <b>Bolt hole circle diameter [mm]</b> | 275              |
| <b>Valve seat</b>                     | External Valve   |
| <b>Valve hole diameter [mm]</b>       | 15.7             |
| <b>Preassembled valve</b>             | No               |
| <b>TPMS-kompatibles Ventil</b>        | No               |