

WHEELS

Product group	Wheels
Item number	10001476
Valid wheel size	315 / 80 R 22.5
Brand	Sailun
Tread pattern	S815
Valid rim size	9.00 x 22.5 H
Rim connection	10/281/335
Bolt hole design	B33
Offset (mm)	+162
Half centre distance (HMA) [mm]	175
Rim colour	Silver
Load capacity complete wheel [kg]	4000
Speed complete wheel [km/h]	120
Nettogewicht [kg] (gültig)	109,77
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



 **SAILUN**
TYRE

Technical Informations

Assembly Item no. Tyres	• 11066349
LI / SI / PR	156 / 150 L (154 / 150 M), 18 PR
Load capacity 1 [kg]	4000
Speed 1 [km/h].	120
Load capacity 2 [kg]	3750
Speed 2 [km/h].	130
Load capacity 3 [kg]	3350

Speed 3 [km/h].	120
Load capacity 4 [kg]	3350
Speed 4 [km/h].	130
Maximum air pressure [bar].	8,50
Axle position truck	FA RA TR
TL/TT	TL
M+S	M+S
3PMSF	3PMSF
Tyre colour	Black
E-Ready	No
Antistatic	No
ECE regulation number	ECE 54 ECE 117
Rolling resistance	D
Wet grip	C
Rolling noise [db].	73
Rolling noise level	B
Section width (mm)	315
Stat. radius (SLR) [mm]	500
Rolling circumference [mm].	3141
Tread depth (mm)	17,0
Assembly Item no. Rim	• 10000368
Load capacity of rim 1 [kg]	4250
Speed Rims 1 [km/h]	130
Maximum speed [km/h].	120
Type of drive	Angetriebene & gezogene Achse
Number of bolt holes	10
hub hole diameter [mm].	281

Bolt hole circle diameter [mm]	335
Bolt hole diameter [mm]	26.0
Bolt hole design EUWA	M22 DS 36
Countersinking	Sphere
Spherical countersink [mm].	R18
Rim centering	BHC
Rim material	steel
RAL	RAL9006
Valve seat	External Valve
Disc thickness [mm]	13.0
Ventilation holes	Yes
Single / multi-part	einteilig
Hump	H
Cavity Sealed	No
Verschweißung beidseitig	No
Assembly Item no. Valve	• 47201040
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve hole diameter [mm]	9.7
Valve design	Metal valve
Valve designation ETRTO	V3.20.1
Valve length [mm]	41.0
Valve angle [°]	gerade