

WHEELS

Product group	Wheels
Item number	10001476
Valid wheel size	315 / 80 R 22.5
Brand	Sailun
Tread pattern	S815
Valid rim size	9.00 x 22.5 H
Rim connection	10/281/335
Bolt hole design	B33
Offset (mm)	+162
Half centre distance (HMA) [mm]	175
Rim colour	Silver
Load capacity complete wheel [kg]	4000
Speed complete wheel [km/h]	120



Technical Informations

Assembly Item no. Tyres	• 11066349
LI / SI / PR	156 / 150 L, 18 PR
Load capacity 1 [kg]	4000
Speed 1 [km/h].	120
Load capacity 3 [kg]	3350
Speed 3 [km/h].	120
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA RA TR
Antistatic	No

Tyre colour	Black
Nettogewicht [kg] (gültig)	109,77
ECE regulation number	ECE 54 ECE 117
Section width (mm)	315
Stat. radius (SLR) [mm]	500.16
Rolling circumference [mm].	3141
Tread depth (mm)	17,0
Rolling resistance	D
Wet grip	C
Rolling noise [db].	73
Rolling noise level	B
E-Ready	No
Assembly Item no. Rim	• 10000368
Load capacity of rim 1 [kg]	4250
Speed Rims 1 [km/h]	130
Maximum speed [km/h].	120
Maximum air pressure [bar].	8,50
Type of drive	Angetriebene & gezogene Achse
Hump	H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Disc thickness [mm]	13.0
Ventilation holes	Yes
Verschweißung beidseitig	No
Rim centering	BHC

Number of bolt holes	10
Bolt hole diameter [mm]	26.0
Countersinking	Sphere
Spherical countersink [mm].	R18
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	9.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V3.20.1
Valve length [mm]	41.0
Valve angle [°]	gerade