

RIMS

Product group	Rims
Item number	10001477
Valid rim size	7.00 I x 12
Rim connection	5/67/112
Bolt hole design	B1
Offset (mm)	+60
Rim colour	Silver
Brand	Fira



Technical Informations

Load capacity of rim 1 [kg]	590
Speed Rims 1 [km/h]	30
Load capacity of rim 2 [kg]	650
Speed Rims 2 [km/h]	30
Load capacity of rim 3 [kg]	545
Speed Rims 3 [km/h]	40
Maximum speed [km/h].	40
Type of drive	Angetriebene & gezogene Achse
Nettogewicht [kg] (gültig)	8,51
Hump	kein Hump
Valve protection	VSH

Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Disc thickness [mm]	7
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	5
Bolt hole design EUWA	B14 DS 28
Bolt hole diameter [mm]	18.5
Countersinking	Sphere
Spherical countersink [mm].	R14
hub hole diameter [mm].	67
Bolt hole circle diameter [mm]	112
Valve seat	External Valve
Valve hole diameter [mm]	11.3
Preassembled valve	No
TPMS-kompatibles Ventil	No