

## RIMS

|                                 |              |
|---------------------------------|--------------|
| Product group                   | Rims         |
| Item number                     | 10001487     |
| Valid rim size                  | 11.75 x 22.5 |
| Rim connection                  | 10/281/335   |
| Bolt hole design                | A3           |
| Offset (mm)                     | -62          |
| Half centre distance (HMA) [mm] | 75           |
| Rim colour                      | Anthrazit    |
| Brand                           | Jantsa       |



## Technical Informations

|                             |                               |
|-----------------------------|-------------------------------|
| Load capacity of rim 1 [kg] | 7500                          |
| Speed Rims 1 [km/h]         | 20                            |
| Load capacity of rim 2 [kg] | 5000                          |
| Speed Rims 2 [km/h]         | 65                            |
| Maximum speed [km/h].       | 65                            |
| Type of drive               | Angetriebene & gezogene Achse |
| Nettogewicht [kg] (gültig)  | 49,50                         |
| Hump                        | kein Hump                     |
| Valve protection            | VS H                          |
| Single / multi-part         | einteilig                     |
| Rim material                | steel                         |

---

|                                       |                  |
|---------------------------------------|------------------|
| <b>RAL</b>                            | RAL9011          |
| <b>Cavity Sealed</b>                  | No               |
| <b>Disc thickness [mm]</b>            | 13               |
| <b>Knurling</b>                       | without knurling |
| <b>Verschweißung beidseitig</b>       | No               |
| <b>Ventilation holes</b>              | No               |
| <b>Rim centering</b>                  | BC               |
| <b>Number of bolt holes</b>           | 10               |
| <b>Bolt hole design EUWA</b>          | B22 ES 36        |
| <b>Bolt hole diameter [mm]</b>        | 27               |
| <b>Countersinking</b>                 | Sphere           |
| <b>Spherical countersink [mm].</b>    | R18              |
| <b>hub hole diameter [mm].</b>        | 281              |
| <b>Bolt hole circle diameter [mm]</b> | 335              |
| <b>Valve seat</b>                     | External Valve   |
| <b>Valve hole diameter [mm]</b>       | 15.7             |
| <b>Preassembled valve</b>             | No               |