

WHEELS

Product group	Wheels
Item number	10001513
Valid wheel size	600 / 50 R 22.5
Brand	BKT
Tread pattern	Ridemax FL 693 M
Valid rim size	AG 20.00 x 22.5 H2
Rim connection	10/281/335
Bolt hole design	A3
Offset (mm)	+65
Rim colour	Silver
Load capacity complete wheel [kg]	5600
Speed complete wheel [km/h]	65
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



Technical Informations

Assembly Item no. Tyres	• 15715133
LI / SI / PR	159 D / 156 E
Load capacity 1 [kg]	4375
Speed 1 [km/h].	65
Load capacity 2 [kg]	4000
Speed 2 [km/h].	70
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black

Nettogewicht [kg] (gültig)	171,73
ECE regulation number	ECE 106
Section width (mm)	611
Stat. radius (SLR) [mm]	516
Rolling circumference [mm].	3574
Tread depth (mm)	21,0
Tyre capacity 75% [ltr.]	340
E-Ready	No
Assembly Item no. Rim	• 10001283
Load capacity of rim 1 [kg]	7600
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	5600
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	65
Maximum air pressure [bar].	4,00
Number of bolt holes	10
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Bolt hole diameter [mm]	27.0
Countersinking	Sphere
Spherical countersink [mm].	R18
Type of drive	Towed axle
Hump	H2
Valve protection	VSH
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel

RAL	RAL9006
Cavity Sealed	No
Disc thickness [mm]	12.0
Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve
Valve hole diameter [mm]	15.0
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade