

TYRES

Product group	Tyres
Item number	10001515
Valid tyre size	710 / 70 R 38
LI / SI / PR	178 A8 / 175 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Factor





Notes and features

- The BKT Agrimax Factor is a new type of 70 series radial tyre for tillage tractors.
- Its tractor pattern with extended lugs provides good ride comfort.
- The reduced lug angle allows for reduced rolling resistance.
- The large contact area ensures smooth running.
- The strong polyester carcass provides excellent lateral stability and steering response even at higher speeds.



Technical Informations

Item number	10001515
EAN	8903094071166
Valid tyre size	710 / 70 R 38
LI / SI / PR	178 A8 / 175 D
TL/TT	TL
Brand	BKT
Tread pattern	Agrimax Factor
Carcass properties	E-Ready
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	297,52
Recommended rim size	DW23B
Permitted rim size	DW25B, MW23B
Maximum air pressure [bar].	3,20
Section width (mm)	716
Tread width (mm)	675
Outer diameter of tyre [mm].	1959
Stat. radius (SLR) [mm]	866
Speed Radius Index (SRI)	925
Rolling circumference [mm].	5800
Tread depth (mm)	58,0
Number of lugs	20x2
E-Ready	Yes

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
178 A8	7500	40		3,20	
175 D	6900	65		3,20	