

TYRES

Product group	Tyres
Item number	10001517
Valid tyre size	600 / 50 - 22.5
LI / SI / PR	155 A8 / 167 A8, 18 PR
TL/TT	TL
Brand	BKT
Tread pattern	Flotation 648



Notes and features

- Bias flotation tyre for mixed use in fields and on roads
- Can be used universally on various agricultural trailers and towed equipment
- Developed for high load capacities, even with low inflation pressure, therefore minimised ground pressure
- Rounded shoulders provide additional protection for green areas and plant stock
- Traction tread pattern with overlapping lugs for good self-cleaning and smooth running

Technical Informations

Item number	10001517
EAN	8903094030781
Valid tyre size	600 / 50 - 22.5
LI / SI / PR	155 A8 / 167 A8, 18 PR
TL/TT	TL
Brand	BKT
Tread pattern	Flotation 648
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	104,34
Recommended rim size	AG20.00
Maximum air pressure [bar].	2,90
Section width (mm)	600
Outer diameter of tyre [mm].	1170
Stat. radius (SLR) [mm]	510
Rolling circumference [mm].	3501
Tread depth (mm)	26,0
Number of lugs	28x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
155 A8	3875	40	Drive Wheel	2,90	LLV
167 A8	5450	40	Free Rolling	2,90	LLV