

## RIMS

|                  |           |
|------------------|-----------|
| Product group    | Rims      |
| Item number      | 10001530  |
| Valid rim size   | W 8 x 15  |
| Rim connection   | 6/161/205 |
| Bolt hole design | B2        |
| Offset (mm)      | +60       |
| Rim colour       | Silver    |
| Brand            | Fira      |



## Technical Informations

|                             |                               |
|-----------------------------|-------------------------------|
| Load capacity of rim 1 [kg] | 1800                          |
| Speed Rims 1 [km/h]         | 40                            |
| Load capacity of rim 2 [kg] | 1620                          |
| Speed Rims 2 [km/h]         | 40                            |
| Maximum speed [km/h].       | 40                            |
| Type of drive               | Angetriebene & gezogene Achse |
| Nettogewicht [kg] (gültig)  | 13,38                         |
| Hump                        | kein Hump                     |
| Valve protection            | VSH                           |
| Single / multi-part         | einteilig                     |
| Rim material                | steel                         |

|                                       |                  |
|---------------------------------------|------------------|
| <b>RAL</b>                            | RAL9006          |
| <b>Cavity Sealed</b>                  | No               |
| <b>Disc thickness [mm]</b>            | 7                |
| <b>Knurling</b>                       | without knurling |
| <b>Verschweißung beidseitig</b>       | No               |
| <b>Ventilation holes</b>              | No               |
| <b>Rim centering</b>                  | BC               |
| <b>Number of bolt holes</b>           | 6                |
| <b>Bolt hole design EUWA</b>          | B18 DS 32        |
| <b>Bolt hole diameter [mm]</b>        | 21.5             |
| <b>Countersinking</b>                 | Sphere           |
| <b>Spherical countersink [mm].</b>    | R16              |
| <b>hub hole diameter [mm].</b>        | 161              |
| <b>Bolt hole circle diameter [mm]</b> | 205              |
| <b>Valve seat</b>                     | External Valve   |
| <b>Valve hole diameter [mm]</b>       | 15.7             |
| <b>Preassembled valve</b>             | No               |
| <b>TPMS-kompatibles Ventil</b>        | No               |