

## **TYRES**

Product group	Tyres	
Item number	10001538	
Valid tyre size	24 R 21	
LI / SI / PR	176 G, 16 PR	
TL/TT	TL	
Brand	ВКТ	
Tread pattern	Earthmax SR 331	





## Notes and features

- The BKT Earthmax SR 331 is an MPT radial tyre for multipurpose and emergency vehicles.
- Its unique block tread maximises the ground contact area to provide very good handling and ride comfort in all conditions.
- The non-directional tread offers very good flotation, traction and self-cleaning properties.
- The tyre is well suited for all surfaces, including soft, sandy or muddy ground.
- The all-steel carcass and steel belt design guarantee a long service life and very good protection against cracks or punctures.



## **Technical Informations**

Item number	10001538
EAN	8903094067671
Valid tyre size	24 R 21
LI / SI / PR	176 G, 16 PR
TL/TT	TL
Brand	BKT
Tread pattern	Earthmax SR 331
M+S	M+S
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54
Nettogewicht [kg] (gültig)	198,03
Recommended rim size	18.0
Maximum air pressure [bar].	5,90
Section width (mm)	606
Outer diameter of tyre [mm].	1382
Stat. radius (SLR) [mm]	628
Rolling circumference [mm].	4194
Tread depth (mm)	24,0
E-Ready	No

## **Load capacity**

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
176 G	7100	90		5,90	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.