

## TYRES

|                 |                      |
|-----------------|----------------------|
| Product group   | Tyres                |
| Item number     | 10001541             |
| Valid tyre size | IF 800 / 70 R 42 CFO |
| LI / SI / PR    | 192 D                |
| TL/TT           | TL                   |
| Brand           | BKT                  |
| Tread pattern   | Agrimax Force        |



Bohnenkamp  
Moving Professionals



## Notes and features

- BKT Agrimax Force is an IF tyre for high performance tractors with more than 250 hp.
- It offers 20% higher load capacity at the same air pressure or the same load capacity at 20% lower air pressure compared to a standard tyre.
- The large contact area enables a uniform distribution of ground pressure and therefore optimum soil protection.
- Its strong polyester belt carcass provides good traction and stability on all surfaces and long tyre life.
- The tyre guarantees driving comfort in the field and during transport trips on the road without the need to adjust the air pressure.

## Technical Informations

|                              |                      |
|------------------------------|----------------------|
| Item number                  | 10001541             |
| EAN                          | 8903094073658        |
| Valid tyre size              | IF 800 / 70 R 42 CFO |
| LI / SI / PR                 | 192 D                |
| TL/TT                        | TL                   |
| Brand                        | BKT                  |
| Tread pattern                | Agrimax Force        |
| Antistatic                   | No                   |
| Tyre colour                  | Black                |
| ECE regulation number        | ECE 106              |
| Nettogewicht [kg] (gültig)   | 454,40               |
| Recommended rim size         | DW27B                |
| Permitted rim size           | DE25B, DW28B, DW30B  |
| Maximum air pressure [bar].  | 3,20                 |
| Section width (mm)           | 794                  |
| Tread width (mm)             | 760                  |
| Outer diameter of tyre [mm]. | 2150                 |
| Stat. radius (SLR) [mm]      | 950                  |
| Rolling circumference [mm].  | 6400                 |
| Tread depth (mm)             | 64,5                 |
| Number of lugs               | 22x2                 |
| E-Ready                      | No                   |

## Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| 192 D | 11200              | 65           |               | 3,20                     |              |