

WHEELS

Product group	Wheels
Item number	10001548
Valid wheel size	275 / 70 R 22.5
Brand	Sailun
Tread pattern	CITYCONVOY
Valid rim size	7.50 x 22.5 H
Rim connection	10/281/335
Bolt hole design	M22
Offset (mm)	+149
Half centre distance (HMA) [mm]	162
Rim colour	Silver
Load capacity complete wheel [kg]	3150
Speed complete wheel [km/h]	100



Technical Informations

Assembly Item no. Tyres	• 11066313
LI / SI / PR	148 / 145 J (152 / 148 F), 16 PR
Load capacity 1 [kg]	3150
Speed 1 [km/h].	100
Load capacity 2 [kg]	3550
Speed 2 [km/h].	80
Load capacity 3 [kg]	2900
Speed 3 [km/h].	100
Load capacity 4 [kg]	3150
Speed 4 [km/h].	80

M+S	M+S
3PMSF	3PMSF
Axle position truck	FA RA TR
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	92,78
ECE regulation number	ECE 54 ECE 117
Section width (mm)	275
Stat. radius (SLR) [mm]	445.18
Rolling circumference [mm].	2922
Tread depth (mm)	20,5
Rolling resistance	D
Wet grip	C
Rolling noise [db].	72
Rolling noise level	B
E-Ready	No
Assembly Item no. Rim	• 10000366
Load capacity of rim 1 [kg]	3550
Speed Rims 1 [km/h]	80
Load capacity of rim 2 [kg]	3250
Speed Rims 2 [km/h]	130
Maximum speed [km/h].	100
Maximum air pressure [bar].	9,00
Type of drive	Angetriebene & gezogene Achse
Hump	H
Single / multi-part	einteilig
Rim material	steel

RAL	RAL9006
Cavity Sealed	No
Disc thickness [mm]	13.0
Ventilation holes	Yes
Verschweißung beidseitig	No
Rim centering	HB
Number of bolt holes	10
Bolt hole diameter [mm]	26.0
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	9.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V3.22.1
Valve length [mm]	58.0
Valve angle [°]	45