

TYRES

Product group	Tyres	
Item number	10001551	
Valid tyre size	800 / 60 R 32	
LI / SI / PR	185 D	
TL/TT	TL	
Brand	Vredestein	
Tread pattern	FLOTATION TRAC	





Notes and features

- The Vredestein Flotation Trac is a radial flotation tyre for arable farming, pastures and transport work.
- The tread pattern is stable in the centre and rounded in the shoulder area for perfect performance.
- Its flexible casing and strong belt construction provide an optimum contact area even under unstable inflation pressure.
- Its firm bead ensures a reliable rim fit.



Technical Informations

Item number	10001551
EAN	8714692291548
Valid tyre size	800 / 60 R 32
LI / SI / PR	185 D
TL/TT	TL
Brand	Vredestein
Tread pattern	FLOTATION TRAC
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	307,47
Recommended rim size	DW 27 B
Maximum air pressure [bar].	4,00
Section width (mm)	800
Outer diameter of tyre [mm].	1795
Stat. radius (SLR) [mm]	810
Speed Radius Index (SRI)	850
Rolling circumference [mm].	5550
Tread depth (mm)	28,0
Tyre capacity 75% [ltr.]	777
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
185 D	9250	65		4,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.