

## WHEELS

|                                   |                    |
|-----------------------------------|--------------------|
| Product group                     | Wheels             |
| Item number                       | 10001557           |
| Valid wheel size                  | 750 / 60 R 30.5    |
| Brand                             | BKT                |
| Tread pattern                     | Ridemax FL 693 M   |
| Valid rim size                    | AG 24.00 x 30.5 H2 |
| Rim connection                    | 10/281/335         |
| Bolt hole design                  | A3                 |
| Offset (mm)                       | -50                |
| Rim colour                        | Black              |
| Load capacity complete wheel [kg] | 8250               |
| Speed complete wheel [km/h]       | 65                 |
| Nettogewicht [kg] (gültig)        | 361,58             |
| RDRA (Reifendruckregelanlage)     | No                 |
| RDKS (Reifendruckkontrollsystem)  | No                 |



## Technical Informations

|                             |            |
|-----------------------------|------------|
| Assembly Item no. Tyres     | • 15715250 |
| LI / SI / PR                | 181 D      |
| Load capacity 1 [kg]        | 8250       |
| Speed 1 [km/h].             | 65         |
| Maximum air pressure [bar]. | 4,00       |
| TL/TT                       | TL         |
| Tyre colour                 | Black      |
| E-Ready                     | No         |

|                                |                |
|--------------------------------|----------------|
| Carcass properties             | Steel Belted   |
| Antistatic                     | No             |
| ECE regulation number          | ECE 106        |
| Section width (mm)             | 754            |
| Stat. radius (SLR) [mm]        | 728            |
| Rolling circumference [mm].    | 5092           |
| Tread depth (mm)               | 26,0           |
| Tyre capacity 75% [litr.]      | 736            |
| Assembly Item no. Rim          | • 10001544     |
| Load capacity of rim 1 [kg]    | 11800          |
| Speed Rims 1 [km/h]            | 40             |
| Load capacity of rim 2 [kg]    | 8700           |
| Speed Rims 2 [km/h]            | 65             |
| Maximum speed [km/h].          | 65             |
| Type of drive                  | Towed axle     |
| Number of bolt holes           | 10             |
| hub hole diameter [mm].        | 281            |
| Bolt hole circle diameter [mm] | 335            |
| Bolt hole diameter [mm]        | 27.0           |
| Bolt hole design EUWA          | B22 ES 36      |
| Countersinking                 | Sphere         |
| Spherical countersink [mm].    | R18            |
| Rim centering                  | BC             |
| Rim material                   | steel          |
| RAL                            | RAL9005        |
| Valve seat                     | External Valve |
| Disc thickness [mm]            | 15.0           |

|                          |                  |
|--------------------------|------------------|
| Ventilation holes        | No               |
| Single / multi-part      | einteilig        |
| Hump                     | H2               |
| Valve protection         | VSH              |
| Cavity Sealed            | No               |
| Knurling                 | without knurling |
| Verschweißung beidseitig | No               |
| Assembly Item no. Valve  | • 47201038       |
| Preassembled valve       | No               |
| TPMS-kompatibles Ventil  | No               |
| Valve hole diameter [mm] | 15.7             |
| Valve design             | Metal valve      |
| Valve designation ETRTO  | V5.01.1          |
| Valve length [mm]        | 50.0             |
| Valve angle [°]          | gerade           |