

## TYRES

Product group	Tyres
Item number	10001567
Valid tyre size	VF 650 / 65 R 38 NRO
LI / SI / PR	169 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agriflex 372 +



## Notes and features

- The Alliance 372+ is a VF tyre for high performance tractors from approx. 220 hp.
- Its extremely flexible sidewalls enable it to carry up to 40% more load capacity at the same inflation pressure or the same load capacity at 40% lower inflation pressure compared with a standard tyre.
- The larger contact area provides excellent traction and consequently reduced fuel costs.
- At the same time, soil compaction is reduced and the soil is optimally protected.
- The R-1W tread pattern ensures excellent grip and a long service life.
- The tyre can be used for cyclic field operation (CFO) on harvesters.

**Technical Informations**

Item number	10001567
EAN	8903635050230
Valid tyre size	VF 650 / 65 R 38 NRO
LI / SI / PR	169 D
TL/TT	TL
Brand	Alliance
Tread pattern	Agriflex 372 +
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	251,80
Recommended rim size	DW23B
Permitted rim size	DW21B
Maximum air pressure [bar].	1,60
Section width (mm)	650
Outer diameter of tyre [mm].	1811
Stat. radius (SLR) [mm]	797.4
Speed Radius Index (SRI)	875
Rolling circumference [mm].	5285
Contact area [cm <sup>2</sup> ]	3183.6
Tread depth (mm)	58,0
Number of lugs	21x2
Tyre capacity 75% [ltr.]	589.95
Guarantee period	10 years
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
169 D	5800	65		1,60	