

TYRES

| Product group | Tyres | |
|-----------------|------------------|--|
| Item number | 10001577 | |
| Valid tyre size | VF 650 / 75 R 38 | |
| LI / SI / PR | 175 D | |
| TL/TT | TL | |
| Brand | Alliance | |
| Tread pattern | Agriflex 372 + | |





Notes and features

- The Alliance 372+ is a VF tyre for high performance tractors from approx. 220 hp.
- Its extremely flexible sidewalls enable it to carry up to 40% more load capacity at the same inflation pressure or the same load capacity at 40% lower inflation pressure compared with a standard tyre.
- The larger contact area provides excellent traction and consequently reduced fuel costs.
- At the same time, soil compaction is reduced and the soil is optimally protected.
- The R-1W tread pattern ensures excellent grip and a long service life.
- The tyre can be used for cyclic field operation (CFO) on harvesters.



Technical Informations

| Item number | 10001577 |
|------------------------------|------------------|
| EAN | 8903635047018 |
| Valid tyre size | VF 650 / 75 R 38 |
| LI / SI / PR | 175 D |
| TL/TT | TL |
| Brand | Alliance |
| Tread pattern | Agriflex 372 + |
| Carcass properties | Steel Belted |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 106 |
| Nettogewicht [kg] (gültig) | 270,00 |
| Recommended rim size | DW23B |
| Permitted rim size | DW21B |
| Maximum air pressure [bar]. | 1,60 |
| Section width (mm) | 666 |
| Outer diameter of tyre [mm]. | 1940 |
| Stat. radius (SLR) [mm] | 840.00 |
| Speed Radius Index (SRI) | 925 |
| Rolling circumference [mm]. | 5702 |
| Contact area [cm²] | 4296.6 |
| Tread depth (mm) | 54,0 |
| Number of lugs | 22x2 |
| Tyre capacity 75% [ltr.] | 755.62 |
| Guarantee period | 10 years |
| E-Ready | No |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|-----------------------------|--------------|
| 175 D | 6900 | 65 | | 1,60 | |