

TYRES

| | |
|-----------------|-------------|
| Product group | Tyres |
| Item number | 10001584 |
| Valid tyre size | 10.00 - 20 |
| LI / SI / PR | 18 PR |
| TL/TT | TT |
| SET | Tube + Flap |
| Brand | BKT |
| Tread pattern | Lug Star |



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- The BKT Lug Star is a specially developed tyre for wheeled excavators.
- With its closed, robust tread center, the tire is excellently suited for use on two-way excavators in rail traffic.

Technical Informations

| | |
|------------------------------|---------------|
| Item number | 10001584 |
| EAN | 8903094073580 |
| Valid tyre size | 10.00 - 20 |
| LI / SI / PR | 18 PR |
| TL/TT | TT |
| SET | Tube + Flap |
| Valve designation | TR 78 A |
| Ventilposition | central |
| Brand | BKT |
| Tread pattern | Lug Star |
| Antistatic | No |
| Tyre colour | Black |
| Nettogewicht [kg] (gültig) | 67,87 |
| Recommended rim size | 7.5 |
| Permitted rim size | 7.0, 8.0 |
| Maximum air pressure [bar]. | 10,00 |
| Section width (mm) | 280 |
| Outer diameter of tyre [mm]. | 1080 |
| Stat. radius (SLR) [mm] | 506 |
| Rolling circumference [mm]. | 3343 |
| Tread depth (mm) | 22,0 |
| E-Ready | No |

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|--------------------------|--------------|
| | 6890 | 10 | | 10,00 | |
| | 5300 | 25 | | 10,00 | |