

TYRES

Product group	Tyres
Item number	10001585
Valid tyre size	320 / 90 R 54
LI / SI / PR	151 D
TL/TT	TL
Brand	Alliance
Tread pattern	350



Notes and features

- Row crop tyre for use on tractors and self-propelled field sprayers.
- Ideal for crop protection and maintenance work on row crops.
- Rounded shoulders protect against plant and soil damage.
- Available in very high load-capacity variants, even for the heaviest combination of machines (field sprayer + additional tank).
- 65 km/h approval (subject to exceptions).

Technical Informations

Item number	10001585
EAN	8903635020042
Valid tyre size	320 / 90 R 54
LI / SI / PR	151 D
TL/TT	TL
Brand	Alliance
Tread pattern	350
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	104,50
Maximum air pressure [bar].	3,60
Section width (mm)	325
Outer diameter of tyre [mm].	1958
Stat. radius (SLR) [mm]	926.6
Speed Radius Index (SRI)	975
Rolling circumference [mm].	5994
Contact area [cm ²]	992.3
Number of lugs	34x2
Tyre capacity 75% [ltr.]	215.25
Guarantee period	7 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
151 D	3450	65		3,60	