

WHEELS

| | |
|-----------------------------------|----------------|
| Product group | Wheels |
| Item number | 10001591 |
| Valid wheel size | 23 x 8.50 - 12 |
| Brand | BKT |
| Tread pattern | LG 306 |
| Valid rim size | 7.00 I x 12 |
| Rim connection | 5/67/112 |
| Bolt hole design | B1 |
| Offset (mm) | +60 |
| Rim colour | Silver |
| Load capacity complete wheel [kg] | 580 |
| Speed complete wheel [km/h] | 30 |
| Nettogewicht [kg] (gültig) | 16,29 |
| RDRA (Reifendruckregelanlage) | No |
| RDKS (Reifendruckkontrollsystem) | No |



Technical Informations

| | |
|-----------------------------|-------------|
| Assembly Item no. Tyres | • 15710480 |
| LI / SI / PR | 89 A6, 6 PR |
| Load capacity 1 [kg] | 580 |
| Speed 1 [km/h]. | 30 |
| Maximum air pressure [bar]. | 2,30 |
| TL/TT | TL |
| Tyre colour | Black |
| E-Ready | No |

| | |
|--------------------------------|-------------------------------|
| Antistatic | No |
| ECE regulation number | ECE 106 |
| Section width (mm) | 210 |
| Stat. radius (SLR) [mm] | 258 |
| Rolling circumference [mm]. | 1709 |
| Tread depth (mm) | 10,0 |
| Assembly Item no. Rim | • 10001477 |
| Load capacity of rim 1 [kg] | 590 |
| Speed Rims 1 [km/h] | 30 |
| Load capacity of rim 2 [kg] | 650 |
| Speed Rims 2 [km/h] | 30 |
| Maximum speed [km/h]. | 30 |
| Type of drive | Angetriebene & gezogene Achse |
| Number of bolt holes | 5 |
| hub hole diameter [mm]. | 67 |
| Bolt hole circle diameter [mm] | 112 |
| Bolt hole diameter [mm] | 18.5 |
| Bolt hole design EUWA | B14 DS 28 |
| Countersinking | Sphere |
| Spherical countersink [mm]. | R14 |
| Rim centering | BC |
| Rim material | steel |
| RAL | RAL9006 |
| Valve seat | External Valve |
| Disc thickness [mm] | 7.0 |
| Ventilation holes | No |
| Single / multi-part | einteilig |

| | |
|--------------------------|--------------|
| Hump | kein Hump |
| Valve protection | VSH |
| Cavity Sealed | No |
| Verschweißung beidseitig | No |
| Assembly Item no. Valve | • 47200650 |
| Preassembled valve | No |
| TPMS-kompatibles Ventil | No |
| Valve hole diameter [mm] | 11.3 |
| Valve design | Rubber valve |
| Valve designation ETRTO | V2.03.1 |
| Valve length [mm] | 43.0 |
| Valve angle [°] | gerade |