

## WHEELS

|                                   |                 |
|-----------------------------------|-----------------|
| Product group                     | Wheels          |
| Item number                       | 10001598        |
| Valid wheel size                  | 23 x 10.50 - 12 |
| Brand                             | BKT             |
| Tread pattern                     | LG 306          |
| Valid rim size                    | 8.50 I x 12 H2  |
| Rim connection                    | 5/67/112        |
| Bolt hole design                  | E1              |
| Rim colour                        | Silver          |
| Load capacity complete wheel [kg] | 710             |
| Speed complete wheel [km/h]       | 30              |
| Nettogewicht [kg] (gültig)        | 18,27           |
| RDRA (Reifendruckregelanlage)     | No              |
| RDKS (Reifendruckkontrollsystem)  | No              |



## Technical Informations

|                             |             |
|-----------------------------|-------------|
| Assembly Item no. Tyres     | • 15710490  |
| LI / SI / PR                | 96 A6, 6 PR |
| Load capacity 1 [kg]        | 710         |
| Speed 1 [km/h].             | 30          |
| Maximum air pressure [bar]. | 2,20        |
| TL/TT                       | TL          |
| Tyre colour                 | Black       |
| E-Ready                     | No          |
| Antistatic                  | No          |

|                                |                |
|--------------------------------|----------------|
| ECE regulation number          | ECE 106        |
| Section width (mm)             | 260            |
| Stat. radius (SLR) [mm]        | 262            |
| Rolling circumference [mm].    | 1697           |
| Tread depth (mm)               | 10,0           |
| Assembly Item no. Rim          | • 31610046     |
| Load capacity of rim 1 [kg]    | 1000           |
| Speed Rims 1 [km/h]            | 30             |
| Load capacity of rim 2 [kg]    | 900            |
| Speed Rims 2 [km/h]            | 40             |
| Maximum speed [km/h].          | 30             |
| Type of drive                  | Towed axle     |
| Number of bolt holes           | 5              |
| hub hole diameter [mm].        | 67             |
| Bolt hole circle diameter [mm] | 112            |
| Bolt hole diameter [mm]        | 18.5           |
| Countersinking                 | Sphere         |
| Spherical countersink [mm].    | R14            |
| Rim centering                  | BC             |
| Rim material                   | steel          |
| RAL                            | RAL9006        |
| Valve seat                     | External Valve |
| Ventilation holes              | No             |
| Single / multi-part            | einteilig      |
| Hump                           | H2             |
| Cavity Sealed                  | No             |
| Verschweißung beidseitig       | No             |

---

|                          |              |
|--------------------------|--------------|
| Assembly Item no. Valve  | • 47200650   |
| Preassembled valve       | No           |
| TPMS-kompatibles Ventil  | No           |
| Valve hole diameter [mm] | 11.3         |
| Valve design             | Rubber valve |
| Valve designation ETRTO  | V2.03.1      |
| Valve length [mm]        | 43.0         |
| Valve angle [°]          | gerade       |