

TYRES

Product group	Tyres
Item number	10001605
Valid tyre size	14.00 - 24 / 10.00
Brand	BKT
Tread pattern	Maglift



Bohnenkamp
■ ■ ● Moving Professionals

BKT
GROWING TOGETHER

Notes and features

- High-quality, 3 layer rubber compound (tread pattern, suspension, basis compound) speaks for the modern, solid rubber tyre design and provides smoothness and ride comfort.
- 4 steel ring packs in the base compound ensure optimal, solid fitting to the rim.
- The hard-wearing tread compound distinguishes itself through a cut-, notch- and heat-resistant compound with high mileage and even wear.
- The BKT Maglift solid rubber tyre, available in standard and LIP design, offers an excellent price-performance ratio.
- All Maglift solid tyres are built in such a way to dissipate static charge from the vehicle.

Technical Informations

Item number	10001605
EAN	8903094073184
Valid tyre size	14.00 - 24 / 10.00
Brand	BKT
Tread pattern	Maglift
Carcass properties	STD,Solid Rubber
Antistatic	Yes
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	358,00
Recommended rim size	10.00
Section width (mm)	330
Side panel width [mm]	330
Tread width (mm)	285
Overall width [mm].	330
Outer diameter of tyre [mm].	1320
Tread depth (mm)	49,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
	11100	25	Load wheel		
	9250	25	Steering wheel		