

TYRES

Product group	Tyres	
Item number	10001613	
Valid tyre size	385 / 55 R 22.5	
LI / SI / PR	160 K, 20 PR	
TL/TT	TL	
Brand	GoodTrip	
Tread pattern	GHT50	





Notes and features

- The GoodTrip GHT50 is a truck trailer tyre for regional transport.
- Its tread pattern with 4 circumferential grooves and a pronounced wide shoulder enables high load capacities and a long service life.
- The special rubber compound ensures low rolling resistance and noise and reduced fuel consumption.
- Stone ejectors in the V-shaped grooves prevent small stones from penetrating and causing tyre damage.



Technical Informations

Item number	10001613
EAN	8859625700862
Valid tyre size	385 / 55 R 22.5
LI / SI / PR	160 K, 20 PR
TL/TT	TL
Brand	GoodTrip
Tread pattern	GHT50
M+S	M+S
3PMSF	3PMSF
Axle position truck	TR
Rolling resistance	В
Wet grip	В
Rolling noise [db].	72
Rolling noise level	В
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54
Nettogewicht [kg] (gültig)	64,08
Recommended rim size	12.25
Permitted rim size	11.75
Maximum air pressure [bar].	9,00
Section width (mm)	386
Tread width (mm)	312
Outer diameter of tyre [mm].	996
Stat. radius (SLR) [mm]	466
Rolling circumference [mm].	3129

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Tread depth (mm)	15,0
E-Ready	No No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
160 K	4500	110	Single	9,00	