

TYRES

Product group	Tyres
Item number	10001614
Valid tyre size	445 / 45 R 19.5
LI / SI / PR	160 J, 22 PR
TL/TT	TL
Brand	GoodTrip
Tread pattern	GHT22



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- The GoodTrip GHT22 is a truck tyre for the trailer axle for long-distance and local transport.
- The bevelled tyre shoulder improves the tyre's heat resistance and thus increases its service life.
- Straight circumferential tread grooves ensure very good water drainage.
- The tread design ensures even ground contact and slow and even wear.

Technical Informations

Item number	10001614
EAN	8859625701043
Valid tyre size	445 / 45 R 19.5
LI / SI / PR	160 J, 22 PR
TL/TT	TL
Brand	GoodTrip
Tread pattern	GHT22
M+S	M+S
3PMSF	3PMSF
Rolling resistance	C
Wet grip	A
Rolling noise [db].	72
Rolling noise level	B
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	63,63
Recommended rim size	15.00
Permitted rim size	14.00
Maximum air pressure [bar].	9,00
Section width (mm)	446
Tread width (mm)	368
Outer diameter of tyre [mm].	895
Stat. radius (SLR) [mm]	418
Rolling circumference [mm].	2812
Tread depth (mm)	13,5

E-Ready

No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
160 J	4500	100	Single	9,00	