

TYRES

| Product group | Tyres | |
|-----------------|-----------------|--|
| Item number | 10001614 | |
| Valid tyre size | 445 / 45 R 19.5 | |
| LI / SI / PR | 160 J, 22 PR | |
| TL/TT | TL | |
| Brand | GoodTrip | |
| Tread pattern | GHT22 | |





Notes and features

- The GoodTrip GHT22 is a truck tyre for the trailer axle for long-distance and local transport.
- Straight circumferential tread grooves ensure very good water drainage.
- The bevelled tyre shoulder improves the tyre's heat resistance and thus increases its service life.
- The tread design ensures even ground contact and slow and even wear.



Technical Informations

| Item number | 10001614 |
|------------------------------|-----------------|
| EAN | 8859625701043 |
| Valid tyre size | 445 / 45 R 19.5 |
| LI / SI / PR | 160 J, 22 PR |
| TL/TT | TL |
| Brand | GoodTrip |
| Tread pattern | GHT22 |
| M+S | M+S |
| 3PMSF | 3PMSF |
| Rolling resistance | С |
| Wet grip | A |
| Rolling noise [db]. | 72 |
| Rolling noise level | В |
| Antistatic | No |
| Tyre colour | Black |
| ECE regulation number | ECE 54,ECE 117 |
| Nettogewicht [kg] (gültig) | 63,63 |
| Recommended rim size | 15.00 |
| Permitted rim size | 14.00 |
| Maximum air pressure [bar]. | 9,00 |
| Section width (mm) | 446 |
| Tread width (mm) | 368 |
| Outer diameter of tyre [mm]. | 895 |
| Stat. radius (SLR) [mm] | 418 |
| Rolling circumference [mm]. | 2812 |
| Tread depth (mm) | 13,5 |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.





| E-Ready No | |
|------------|--|
|------------|--|

Load capacity

| Index | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure [bar] | Load variant |
|-------|--------------------|--------------|---------------|-----------------------------|--------------|
| 160 J | 4500 | 100 | Single | 9,00 | |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.