

TYRES

Product group	Tyres
Item number	10001616
Valid tyre size	385 / 65 R 22.5
LI / SI / PR	160 K (158 L)
TL/TT	TL
Brand	Semperit
Tread pattern	Runner F2



Bohnenkamp
■ ■ ● Moving Professionals

SEMPERIT 
Seit 1906.

Notes and features

- The Semperit Runner F2 is a truck tyre for steering axles for regional and long-distance transport.
- Its tread pattern design with flexible sipes guarantees excellent handling, even on wet roads.
- The optimum contact area and the special rubber compound ensure slow wear and high mileage.

Technical Informations

Item number	10001616
EAN	4024067005002
Valid tyre size	385 / 65 R 22.5
LI / SI / PR	160 K (158 L)
TL/TT	TL
Brand	Semperit
Tread pattern	Runner F2
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA
Rolling resistance	C
Wet grip	C
Rolling noise [db].	73
Rolling noise level	B
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 117,ECE 54
Nettogewicht [kg] (gültig)	68,40
Recommended rim size	11.75
Maximum air pressure [bar].	9,00
Section width (mm)	377
Tread width (mm)	299
Outer diameter of tyre [mm].	1063
Stat. radius (SLR) [mm]	494
Rolling circumference [mm].	3274
Tread depth (mm)	14,5

E-Ready	No
---------	----

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
160 K	4500	110	Single	9,00	
158 L	4250	120	Single	9,00	