

## WHEELS

|                                   |                    |
|-----------------------------------|--------------------|
| Product group                     | Wheels             |
| Item number                       | 10001620           |
| Valid wheel size                  | 600 / 50 R 22.5    |
| Brand                             | BKT                |
| Tread pattern                     | Ridemax FL 693 M   |
| Valid rim size                    | AG 20.00 x 22.5 H2 |
| Rim connection                    | 10/281/335         |
| Bolt hole design                  | B3                 |
| Offset (mm)                       | +50                |
| Rim colour                        | Silver             |
| Load capacity complete wheel [kg] | 4375               |
| Speed complete wheel [km/h]       | 65                 |
| RDRA (Reifendruckregelanlage)     | No                 |
| RDKS (Reifendruckkontrollsystem)  | No                 |



## Technical Informations

|                         |               |
|-------------------------|---------------|
| Assembly Item no. Tyres | • 15715133    |
| LI / SI / PR            | 159 D / 156 E |
| Load capacity 1 [kg]    | 4375          |
| Speed 1 [km/h].         | 65            |
| Load capacity 2 [kg]    | 4000          |
| Speed 2 [km/h].         | 70            |
| Carcass properties      | Steel Belted  |
| Antistatic              | No            |
| Tyre colour             | Black         |

|                                |            |
|--------------------------------|------------|
| Nettogewicht [kg] (gültig)     | 172,73     |
| ECE regulation number          | ECE 106    |
| Section width (mm)             | 611        |
| Stat. radius (SLR) [mm]        | 516        |
| Rolling circumference [mm].    | 3574       |
| Tread depth (mm)               | 21,0       |
| Tyre capacity 75% [ltr.]       | 340        |
| E-Ready                        | No         |
| Assembly Item no. Rim          | • 10001188 |
| Load capacity of rim 1 [kg]    | 7600       |
| Speed Rims 1 [km/h]            | 40         |
| Load capacity of rim 2 [kg]    | 5600       |
| Speed Rims 2 [km/h]            | 65         |
| Maximum speed [km/h].          | 70         |
| Maximum air pressure [bar].    | 4,00       |
| Number of bolt holes           | 10         |
| Bolt hole design EUWA          | B22 DS 36  |
| hub hole diameter [mm].        | 281        |
| Bolt hole circle diameter [mm] | 335        |
| Bolt hole diameter [mm]        | 27.0       |
| Countersinking                 | Sphere     |
| Spherical countersink [mm].    | R18        |
| Type of drive                  | Towed axle |
| Hump                           | H2         |
| Valve protection               | VSH        |
| Single / multi-part            | einteilig  |
| Rim centering                  | BC         |

---

|                          |                  |
|--------------------------|------------------|
| Rim material             | steel            |
| RAL                      | RAL9006          |
| Cavity Sealed            | No               |
| Disc thickness [mm]      | 12.0             |
| Knurling                 | without knurling |
| Ventilation holes        | No               |
| Verschweißung beidseitig | No               |
| Valve seat               | External Valve   |
| Valve hole diameter [mm] | 15.7             |
| Preassembled valve       | No               |
| TPMS-kompatibles Ventil  | No               |
| Valve design             | Metal valve      |
| Valve designation ETRTO  | V5.01.1          |
| Valve length [mm]        | 50.0             |
| Valve angle [°]          | gerade           |