

## WHEELS

Product group	Wheels
Item number	10001621
Valid wheel size	445 / 65 R 22.5
Brand	Windpower
Tread pattern	WE 77
Valid rim size	14.00 x 22.5
Rim connection	10/281/335
Bolt hole design	B33
Offset (mm)	-50
Rim colour	Silver
Load capacity complete wheel [kg]	5350
Speed complete wheel [km/h]	80
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



**WINDPOWER**  
Get Your Job Done

## Technical Informations

Assembly Item no. Tyres	• 10436010
LI / SI / PR	169 F
Load capacity 1 [kg]	5800
Speed 1 [km/h].	80
M+S	M+S
Carcass properties	POR
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	159,90

ECE regulation number	not necessary
Section width (mm)	443
Stat. radius (SLR) [mm]	525
Rolling circumference [mm].	3504
Tread depth (mm)	16,5
E-Ready	No
Assembly Item no. Rim	• 33060307
Load capacity of rim 1 [kg]	5350
Speed Rims 1 [km/h]	80
Load capacity of rim 2 [kg]	5150
Speed Rims 2 [km/h]	100
Maximum speed [km/h].	80
Maximum air pressure [bar].	8,20
Number of bolt holes	10
Bolt hole design EUWA	M22 DS 36
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Bolt hole diameter [mm]	26
Countersinking	Sphere
Spherical countersink [mm].	R18
Type of drive	Angetriebene & gezogene Achse
Hump	kein Hump
Single / multi-part	einteilig
Rim centering	BHC
Rim material	steel
RAL	RAL9006
Cavity Sealed	No

---

Ventilation holes	No
Verschweißung beidseitig	No
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade