

RIMS

Product group	Rims
Item number	10001641
Valid rim size	9.00 x 15.3
Rim connection	6/161/205
Bolt hole design	A2
Offset (mm)	+40
Rim colour	Silver
Brand	Jantsa



Technical Informations

Load capacity of rim 1 [kg]	3250
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	2750
Speed Rims 2 [km/h]	40
Load capacity of rim 3 [kg]	3650
Speed Rims 3 [km/h]	15
Load capacity of rim 4 [kg]	3050
Speed of wheels 4 [km/h].	30
Maximum speed [km/h].	40
Type of drive	Towed axle
Nettogewicht [kg] (gültig)	15,00

Hump	kein Hump
Valve protection	VSH
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Disc thickness [mm]	8
Knurling	without knurling
Verschweißung beidseitig	No
Ventilation holes	No
Rim centering	BC
Number of bolt holes	6
Bolt hole design EUWA	B18 ES 32
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No