

TYRES

Product group	Tyres	
Item number	10001645	
Valid tyre size	420 / 85 R 24	
LI / SI / PR	137 A8 / 137 B	
TL/TT	TL	
Brand	Alliance	
Tread pattern	FarmPRO II	
Sonderpostenkategorie	Disassambled	
type of damage	Dismounted	





Notes and features

- 70 series agricultural tyre for tractors in the low- to medium-power range up to approx. 180 hp (except 710 width).
- All-round tyre for use on farmland and grassland.
- R-1W drive tread pattern with high multi-angle lugs ensures good traction on wet ground.
- Reinforced beads and sidewalls as well as a wide lug contact area in the centre provide high ride comfort.



Technical Informations

Item number	10001645
EAN	4040658113925
Valid tyre size	420 / 85 R 24
Alternative size 1	16.9R24
LI / SI / PR	137 A8 / 137 B
TL/TT	TL
Brand	Alliance
Tread pattern	FarmPRO II
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	87,30
Maximum air pressure [bar].	1,60
Section width (mm)	418
Outer diameter of tyre [mm].	1315
Stat. radius (SLR) [mm]	591
Rolling circumference [mm].	3879
Tread depth (mm)	47,0
Number of lugs	19x2
Tyre capacity 75% [ltr.]	213
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
137 A8	2300	40		1,60	
137 B	2300	50		1,60	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.