

## WHEELS

Product group	Wheels
Item number	10001659
Valid wheel size	300 / 60 - 12
Brand	BKT
Tread pattern	Trac Master
Valid rim size	10.50 I x 12 H2
Rim connection	5/66.6/112
Bolt hole design	A1
Offset (mm)	-70
Rim colour	Silver
Load capacity complete wheel [kg]	1075
Speed complete wheel [km/h]	40
Nettogewicht [kg] (gültig)	28,66
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



## Technical Informations

Assembly Item no. Tyres	• 15710580
LI / SI / PR	109 B, 8 PR
Load capacity 1 [kg]	1030
Speed 1 [km/h].	50
Maximum air pressure [bar].	3,20
TL/TT	TL
Tyre colour	Black
E-Ready	No

Antistatic	No
ECE regulation number	ECE 106
Section width (mm)	306
Stat. radius (SLR) [mm]	285
Rolling circumference [mm].	1885
Tread depth (mm)	18,0
Assembly Item no. Rim	• 31610052
Load capacity of rim 1 [kg]	1075
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	1200
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	40
Type of drive	Towed axle
Number of bolt holes	5
hub hole diameter [mm].	66.6
Bolt hole circle diameter [mm]	112
Bolt hole diameter [mm]	18.5
Bolt hole design EUWA	B14 ES 28
Countersinking	Sphere
Spherical countersink [mm].	R14
Rim centering	BC
Rim material	steel
RAL	RAL9006
Valve seat	External Valve
Disc thickness [mm]	8.0
Ventilation holes	No
Single / multi-part	einteilig

---

Hump	H2
Cavity Sealed	No
Knurling	without knurling
Verschweißung beidseitig	No
Assembly Item no. Valve	• 47200650
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve hole diameter [mm]	11.3
Valve design	Rubber valve
Valve designation ETRTO	V2.03.1
Valve length [mm]	43.0
Valve angle [°]	gerade