

TYRES

Product group	Tyres
Item number	10001667
Valid tyre size	12.00 - 24
LI / SI / PR	24 PR
TL/TT	тт
Brand	ВКТ
Tread pattern	Container King



Notes and features

- The wide central rib creates a large contact surface and provides for outstanding stability when lifting heavy weights
- The strong casing and special hard-wearing running surface compound provide for excellent durability and a long service life
- Best suited for container handlers, such as reach stackers



Technical Informations

Item number	10001667
EAN	8903094069798
Valid tyre size	12.00 - 24
LI / SI / PR	24 PR
TL/TT	TT
Brand	BKT
Tread pattern	Container King
TRA Code	IND4
Antistatic	No
Tyre colour	Black
ECE regulation number	not necessary
Nettogewicht [kg] (gültig)	119,63
Recommended rim size	8.5
Permitted rim size	8.0
Maximum air pressure [bar].	10,00
Section width (mm)	330
Outer diameter of tyre [mm].	1285
Tread depth (mm)	33,5
Number of lugs	28x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
	9510	25		10,00	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.