

## TYRES

Product group	Tyres
Item number	10001669
Valid tyre size	480 / 80 R 26
LI / SI / PR	167 A8 / 167 B
TL/TT	TL
Brand	BKT
Tread pattern	Multimax MP 522



## Notes and features

- Agro-industrial / MPT tyres for telescopic handlers, wheel loaders and backhoe loaders.
- Radial carcass with reinforcing steel belt for high load capacity and protection against puncture damage.
- Aggressive tread lugs for traction under any working conditions.
- Special rubber compound for hard terrain.
- Deep tread depth for a long service life.

## Technical Informations

Item number	10001669
EAN	8903094073108
Valid tyre size	480 / 80 R 26
LI / SI / PR	167 A8 / 167 B
TL/TT	TL
Brand	BKT
Tread pattern	Multimax MP 522
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	133,86
Recommended rim size	DW15L
Permitted rim size	DW16L
Maximum air pressure [bar].	4,00
Section width (mm)	479
Outer diameter of tyre [mm].	1428
Stat. radius (SLR) [mm]	638
Speed Radius Index (SRI)	675
Rolling circumference [mm].	4287
Tread depth (mm)	41,5
Number of lugs	20x2
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
167 A8	5450	40		4,00	
167 B	5450	50		4,00	