

TYRES

Product group	Tyres
Item number	10001684
Valid tyre size	380 / 105 R 50
LI / SI / PR	171 A8 / 168 D
TL/TT	TL
Brand	Alliance
Tread pattern	350





Notes and features

- Row crop tyre for use on tractors and self-propelled field sprayers.
- Ideal for crop protection and maintenance work on row crops.
- Rounded shoulders protect against plant and soil damage.
- Available in very high load-capacity variants, even for the heaviest combination of machines (field sprayer + additional tank).
- 65 km/h approval (subject to exceptions).



Technical Informations

Item number	10001684
EAN	8903635034667
Valid tyre size	380 / 105 R 50
LI / SI / PR	171 A8 / 168 D
TL/TT	TL
Brand	Alliance
Tread pattern	350
TRA Code	R1
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	179,70
Recommended rim size	W12B
Permitted rim size	W13B, DW13B
Maximum air pressure [bar].	4,40
Section width (mm)	405
Outer diameter of tyre [mm].	2050
Stat. radius (SLR) [mm]	952
Speed Radius Index (SRI)	975
Rolling circumference [mm].	6196
Contact area [cm²]	1785.9
Tread depth (mm)	39,0
Number of lugs	33x2
Guarantee period	10 years
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
171 A8	6150	40		4,40	
168 D	5600	65		4,40	