

WHEELS

| | |
|-----------------------------------|-----------------|
| Product group | Wheels |
| Item number | 10001685 |
| Valid wheel size | 245 / 70 R 17.5 |
| Brand | Sailun |
| Tread pattern | SAR1 |
| Valid rim size | 6.75 x 17.5 |
| Rim connection | 10/176/225 |
| Bolt hole design | B33 |
| Offset (mm) | +129.25 |
| Half centre distance (HMA) [mm] | 141 |
| Rim colour | Silver |
| Load capacity complete wheel [kg] | 2725 |
| Speed complete wheel [km/h] | 100 |



Technical Informations

| | |
|-------------------------|----------------------------------|
| Assembly Item no. Tyres | • 11066136 |
| LI / SI / PR | 143 / 141 J (146 / 146 F), 18 PR |
| Load capacity 1 [kg] | 2725 |
| Speed 1 [km/h]. | 100 |
| Load capacity 2 [kg] | 3000 |
| Speed 2 [km/h]. | 80 |
| Load capacity 3 [kg] | 2575 |
| Speed 3 [km/h]. | 100 |
| Load capacity 4 [kg] | 3000 |
| Speed 4 [km/h]. | 80 |

| | |
|-----------------------------|----------------------------------|
| M+S | M+S |
| 3PMSF | 3PMSF |
| Axle position truck | FA TR |
| Antistatic | No |
| Tyre colour | Black |
| Nettogewicht [kg] (gültig) | 57,81 |
| ECE regulation number | ECE 54 ECE 117 Vecto Certificate |
| Section width (mm) | 245 |
| Stat. radius (SLR) [mm] | 364.36 |
| Rolling circumference [mm]. | 2299 |
| Tread depth (mm) | 13,0 |
| Rolling resistance | D |
| Wet grip | B |
| Rolling noise [db]. | 73 |
| Rolling noise level | B |
| E-Ready | No |
| Assembly Item no. Rim | • 10000362 |
| Load capacity of rim 1 [kg] | 3000 |
| Speed Rims 1 [km/h] | 80 |
| Load capacity of rim 2 [kg] | 2750 |
| Speed Rims 2 [km/h] | 130 |
| Maximum speed [km/h]. | 100 |
| Maximum air pressure [bar]. | 8,75 |
| Type of drive | Angetriebene & gezogene Achse |
| Hump | kein Hump |
| Single / multi-part | einteilig |
| Rim material | steel |

| | |
|---------------------------------------|----------------|
| RAL | RAL9006 |
| Cavity Sealed | No |
| Disc thickness [mm] | 11.75 |
| Ventilation holes | Yes |
| Verschweißung beidseitig | No |
| Rim centering | BHC |
| Number of bolt holes | 10 |
| Bolt hole diameter [mm] | 26.0 |
| Countersinking | Sphere |
| Spherical countersink [mm]. | R18 |
| hub hole diameter [mm]. | 176 |
| Bolt hole circle diameter [mm] | 225 |
| Valve seat | Internal Valve |
| Valve hole diameter [mm] | 9.7 |
| Preassembled valve | No |