

## TYRES

Product group	Tyres
Item number	10001688
Valid tyre size	340 / 80 R 24
LI / SI / PR	140 A8 / 135 D
TL/TT	TL
Brand	Alliance
Tread pattern	Multiuse 550



## Notes and features

- Municipal tyres for varied use, e.g. for tractors in contracting services with high road use or for green fodder and corn harvesting.
- Optimal winter performance due to special block tread pattern.
- Low rolling resistance ensures high fuel savings compared with standard agricultural tyres.
- Steel belt reinforcement for high load capacity and protection against punctures.
- With M+S identification.

## Technical Informations

Item number	10001688
EAN	8903635034582
Valid tyre size	340 / 80 R 24
Alternative size 1	12.5R24
LI / SI / PR	140 A8 / 135 D
TL/TT	TL
Brand	Alliance
Tread pattern	Multiuse 550
M+S	M+S
TRA Code	R4
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	67,40
Recommended rim size	DW11
Permitted rim size	DW10, W11, DW12, W12
Maximum air pressure [bar].	3,20
Section width (mm)	343
Outer diameter of tyre [mm].	1154
Stat. radius (SLR) [mm]	529
Speed Radius Index (SRI)	550
Rolling circumference [mm].	3439
Contact area [cm <sup>2</sup> ]	744.5
Tread depth (mm)	24,9
Number of lugs	21x2

Guarantee period	5 years
E-Ready	No

## Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
140 A8	2500	40		3,20	
135 D	2180	65		3,20	