

TYRES

Product group	Tyres
Item number	10001691
Valid tyre size	315 / 80 R 22.5
LI / SI / PR	158 / 156 G (156 / 150 K)
TL/TT	TL
Brand	Bridgestone
Tread pattern	M840 EVO
Sonderpostenkategorie	Remaining stock



Bohnenkamp
Moving Professionals

BRIDGESTONE

Technical Informations

Item number	10001691
EAN	4040658114311
Valid tyre size	315 / 80 R 22.5
LI / SI / PR	158 / 156 G (156 / 150 K)
TL/TT	TL
Brand	Bridgestone
Tread pattern	M840 EVO
M+S	M+S
3PMSF	3PMSF
Axle position truck	FA/RA/TR
Rolling resistance	D

Wet grip	C
Rolling noise [db].	70
Rolling noise level	A
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 117,ECE 54
Nettogewicht [kg] (gültig)	66,20
Recommended rim size	9.00
Permitted rim size	9.75
Section width (mm)	312
Outer diameter of tyre [mm].	1076
Tread depth (mm)	17,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
158 G	4250	90	Single		
156 K	4000	110	Single		
156 G	4000	90	Twin		
150 K	3350	110	Twin		