

TYRES

Product group	Tyres
Item number	10001692
Valid tyre size	540 / 65 R 30
LI / SI / PR	150 D / 147 E
TL/TT	TL
Brand	Bridgestone
Tread pattern	VX-Tractor
Sonderpostenkategorie	Disassembled
type of damage	Dismounted



BRIDGESTONE

Notes and features

- The Bridgestone VX-Tractor is radial tyre for tractors for combined use in the field and on the road.
- Its tractor tread pattern with extra high lug volume due to long and high lugs ensures good traction and slow wear.
- The rubber compound is particularly resistant to damage and wear.
- The carcass construction with reinforced sidewall and 6-ply premium belt guarantees long life and puncture resistance even when driving with high air pressure.

Technical Informations

Item number	10001692
EAN	4040658114328
Valid tyre size	540 / 65 R 30
LI / SI / PR	150 D / 147 E
TL/TT	TL
Brand	Bridgestone
Tread pattern	VX-Tractor
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	147,97
Recommended rim size	DW16L
Permitted rim size	W16L, DW18L, W18L
Maximum air pressure [bar].	2,40
Section width (mm)	530
Outer diameter of tyre [mm].	1474
Stat. radius (SLR) [mm]	668
Speed Radius Index (SRI)	700
Rolling circumference [mm].	4422
Tread depth (mm)	50,0
Number of lugs	19x2
Tyre capacity 75% [litr.]	307
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
150 D	3350	65		2,40	
147 E	3075	70		2,40	