

TYRES

Product group	Tyres
Item number	10001733
Valid tyre size	380 / 90 R 50
LI / SI / PR	161 A8 / 158 D
TL/TT	TL
Brand	Alliance
Tread pattern	350



Notes and features

- Row crop tyre for use on tractors and self-propelled field sprayers.
- Ideal for crop protection and maintenance work on row crops.
- Rounded shoulders protect against plant and soil damage.
- Available in very high load-capacity variants, even for the heaviest combination of machines (field sprayer + additional tank).
- 65 km/h approval (subject to exceptions).

Technical Informations

Item number	10001733
EAN	8903635046653
Valid tyre size	380 / 90 R 50
Alternative size 1	14.5R50
LI / SI / PR	161 A8 / 158 D
TL/TT	TL
Brand	Alliance
Tread pattern	350
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	146,40
Recommended rim size	W12
Permitted rim size	DW12A, W13
Maximum air pressure [bar].	3,60
Section width (mm)	384
Outer diameter of tyre [mm].	1950
Stat. radius (SLR) [mm]	917
Speed Radius Index (SRI)	975
Rolling circumference [mm].	5916
Contact area [cm ²]	1286.7
Tread depth (mm)	47,0
Number of lugs	33x2
Guarantee period	10 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
161 A8	4625	40		3,60	
158 D	4250	65		3,60	