

TYRES

Product group	Tyres
Item number	10001739
Valid tyre size	280 / 80 R 20
LI / SI / PR	133 A8 / 133 B
TL/TT	TL
Brand	Alliance
Tread pattern	Agro Industrial 580



Notes and features

- Agro-industrial / MPT tyre for telescopic-, wheel- and backhoe loaders.
- Strong radial casing ensures high load capacities and maximum stability in use.
- Optimised rubber compound and angled centre lugs for hard surfaces.
- High wear resistance and consequently a long service life.
- Ideal for biogas plants.

Technical Informations

Item number	10001739
EAN	8903635044505
Valid tyre size	280 / 80 R 20
Alternative size 1	10.5R20
LI / SI / PR	133 A8 / 133 B
TL/TT	TL
Brand	Alliance
Tread pattern	Agro Industrial 580
TRA Code	R4
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	39,80
Recommended rim size	W9
Permitted rim size	W8, W10
Maximum air pressure [bar].	4,00
Section width (mm)	282
Outer diameter of tyre [mm].	956
Stat. radius (SLR) [mm]	437
Speed Radius Index (SRI)	450
Rolling circumference [mm].	2846
Tread depth (mm)	33,0
Number of lugs	17x2
Guarantee period	5 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
133 A8	2060	40		4,00	
133 B	2060	50		4,00	