

TYRES

Product group	Tyres
Item number	10001751
Valid tyre size	650 / 75 R 32
LI / SI / PR	172 A8 / 172 B
TL/TT	TL
Brand	Alliance
Tread pattern	Agristar 375



Notes and features

- Super-volume tyre for harvesters, self-propelled machinery for spreading nutrients and other heavy farm machinery.
- Aggressive R-1W tread pattern for maximum traction and low slip.
- Offers enormous load capacities even at low inflation pressures.
- Steel belts and a special stubble guard rubber compound make the tyre even tougher against punctures from corn stubble, for example.

Technical Informations

Item number	10001751
EAN	8903635013914
Valid tyre size	650 / 75 R 32
LI / SI / PR	172 A8 / 172 B
TL/TT	TL
Brand	Alliance
Tread pattern	Agristar 375
TRA Code	R1-W
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	273,90
Recommended rim size	DW21B
Permitted rim size	DW20B, DW23B
Maximum air pressure [bar].	3,20
Section width (mm)	650
Outer diameter of tyre [mm].	1830
Stat. radius (SLR) [mm]	839
Speed Radius Index (SRI)	850
Rolling circumference [mm].	5450
Contact area [cm ²]	2629.4
Tread depth (mm)	58,0
Number of lugs	20x2
Guarantee period	10 years
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
172 A8	6300	40		3,20	
172 B	6300	50		3,20	