# Bohnenkamp Moving Professionals

TYRES

| Product group   | Tyres          |
|-----------------|----------------|
| Item number     | 10001752       |
| Valid tyre size | 800 / 65 R 32  |
| LI / SI / PR    | 172 A8 / 172 B |
| TL/TT           | TL             |
| Brand           | Alliance       |
| Tread pattern   | Agristar 375   |





#### Notes and features

- Super-volume tyre for harvesters, self-propelled machinery for spreading nutrients and other heavy farm machinery.
- Aggressive R-1W tread pattern for maximum traction and low slip.
- Offers enormous load capacities even at low inflation pressures.
- Steel belts and a special stubble guard rubber compound make the tyre even tougher against punctures from corn stubble, for example.

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

# Bohnenkamp Moving Professionals

#### **Technical Informations**

| Item number                  | 10001752       |
|------------------------------|----------------|
| EAN                          | 8903635013907  |
| Valid tyre size              | 800 / 65 R 32  |
| LI / SI / PR                 | 172 A8 / 172 B |
| TL/TT                        | TL             |
| Brand                        | Alliance       |
| Tread pattern                | Agristar 375   |
| TRA Code                     | R1-W           |
| Carcass properties           | Steel Belted   |
| Antistatic                   | No             |
| Tyre colour                  | Black          |
| ECE regulation number        | ECE 106        |
| Nettogewicht [kg] (gültig)   | 340,20         |
| Recommended rim size         | DW27A          |
| Maximum air pressure [bar].  | 2,70           |
| Section width (mm)           | 812            |
| Outer diameter of tyre [mm]. | 1845           |
| Stat. radius (SLR) [mm]      | 845            |
| Rolling circumference [mm].  | 5529           |
| Guarantee period             | 10 years       |
| E-Ready                      | No             |

### Load capacity

| Index  | Load capacity [kg] | Speed [km/h] | Axle position | Inflation pressure<br>[bar] | Load variant |
|--------|--------------------|--------------|---------------|-----------------------------|--------------|
| 172 A8 | 6300               | 40           |               | 2,40                        |              |
| 172 B  | 6300               | 50           |               | 2,40                        |              |

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes.Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.