Bohnenkamp Moving Professionals

TYRES

Product group	Tyres
Item number	10001796
Valid tyre size	540 / 65 R 28
LI / SI / PR	160 A8 / 155 D
TL/TT	TL
Brand	Nokian
Tread pattern	Hakkapeliitta TRI



Notes and features

- Innovative winter tyre for tractors.
- Precise steering and efficiency: specially-developed compound for low temperatures and icy surfaces. Revolutionary tread design with sipes and activators.
- First-class ride comfort: low vibration resembling the performance of car and truck tyres.
- Excellent traction and lateral grip: more grip edges in contact with the road surface.
- Evenly-distributed surface pressure ensures good grip.

18.11.2024

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.

Bohnenkamp Moving Professionals

Technical Informations

Item number	10001796
EAN	6419440473055
Valid tyre size	540 / 65 R 28
LI / SI / PR	160 A8 / 155 D
TL/TT	TL
Brand	Nokian
Tread pattern	Hakkapeliitta TRI
M+S	M+S
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	113,22
Recommended rim size	DW18L
Permitted rim size	DW16L
Maximum air pressure [bar].	3,20
Section width (mm)	535
Outer diameter of tyre [mm].	1398
Dynamic radius [mm]	675
Speed Radius Index (SRI)	675
Tread depth (mm)	28,0
Tyre capacity 75% [ltr.]	320.00
E-Ready	No

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
160 A8	4500	40		3,20	
155 D	3875	65		3,20	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp SE accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.