

TYRES

Product group	Tyres
Item number	10001809
Valid tyre size	340 / 85 R 24
LI / SI / PR	125 A8 / 125 B
TL/TT	TL
Brand	Vredestein
Tread pattern	TRAXION 85 II



Bohnenkamp
■ ■ ● Moving Professionals



Notes and features

- The Traxion 85 II is a standard radial tractor tyre for mid-range tractors.
- Its special tread pattern with curved lugs provides good traction and self-cleaning.
- The bead is reinforced by additional plies, ensuring optimum stability even at higher speeds.
- Furthermore, the tyre distinguishes itself through low slip, high ride comfort and a long service life

Technical Informations

Item number	10001809
EAN	8714692350580
Valid tyre size	340 / 85 R 24
LI / SI / PR	125 A8 / 125 B
TL/TT	TL
Brand	Vredestein
Tread pattern	TRAXION 85 II
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	61,59
Recommended rim size	W12
Permitted rim size	W11, W12L
Maximum air pressure [bar].	1,60
Section width (mm)	360
Outer diameter of tyre [mm].	1195
Stat. radius (SLR) [mm]	545
Speed Radius Index (SRI)	575
Rolling circumference [mm].	3520
Tread depth (mm)	43,0
Tyre capacity 75% [ltr.]	125.0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
125 A8	1650	40		1,60	
125 B	1650	50		1,60	