

## WHEELS

Product group	Wheels
Item number	10001823
Valid wheel size	10 - 16.5
Brand	BKT
Tread pattern	Sure Trax HD
Valid rim size	8.25 x 16.5
Rim connection	6/161/205
Bolt hole design	A2
Rim colour	Silver
Load capacity complete wheel [kg]	1400
Speed complete wheel [km/h]	40
RDRA (Reifendruckregelanlage)	No
RDKS (Reifendruckkontrollsystem)	No



## Technical Informations

Assembly Item no. Tyres	• 15772116
LI / SI / PR	120 A8, 10 PR
Load capacity 1 [kg]	1400
Speed 1 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	45,35
ECE regulation number	ECE 106
Section width (mm)	268
Stat. radius (SLR) [mm]	359

Rolling circumference [mm].	2316
Tread depth (mm)	19,0
E-Ready	No
Assembly Item no. Rim	• 10000926
Load capacity of rim 1 [kg]	2350
Speed Rims 1 [km/h]	25
Load capacity of rim 2 [kg]	2800
Speed Rims 2 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	5,20
Number of bolt holes	6
hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16
Type of drive	Towed axle
Hump	kein Hump
Valve protection	VSH
Single / multi-part	einteilig
Rim centering	BC
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Disc thickness [mm]	8.0
Knurling	without knurling
Ventilation holes	No

---

Verschweißung beidseitig	No
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
TPMS-kompatibles Ventil	No
Valve design	Metal valve
Valve length [mm]	57