

## WHEELS

Product group	Wheels
Item number	10001826
Valid wheel size	VF 800 / 60 R 32
Brand	Alliance
Tread pattern	Agriflex 389 +
Valid rim size	TW 27 B x 32
Rim connection	10/281/335
Bolt hole design	B3
Offset (mm)	+30
Rim colour	Silver
Load capacity complete wheel [kg]	10000
Speed complete wheel [km/h]	65



## Technical Informations

Assembly Item no. Tyres	• 15215819
LI / SI / PR	188 D
Load capacity 1 [kg]	10000
Speed 1 [km/h].	65
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	432,35
ECE regulation number	ECE 106
Section width (mm)	800
Stat. radius (SLR) [mm]	778

Rolling circumference [mm].	5465
Tread depth (mm)	26,0
Number of lugs	28x2
Tyre capacity 75% [ltr.]	877.5
E-Ready	No
Assembly Item no. Rim	• 32013511
Load capacity of rim 1 [kg]	13300
Speed Rims 1 [km/h]	40
Load capacity of rim 2 [kg]	10000
Speed Rims 2 [km/h]	65
Maximum speed [km/h].	65
Maximum air pressure [bar].	2,80
Type of drive	Towed axle
Hump	kein Hump
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Disc thickness [mm]	15
Knurling	without knurling
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	10
Bolt hole design EUWA	B22 DS 36
Bolt hole diameter [mm]	27.0
Countersinking	Sphere

---

Spherical countersink [mm].	R18
hub hole diameter [mm].	281
Bolt hole circle diameter [mm]	335
Valve seat	External Valve
Valve hole diameter [mm]	15.7
Preassembled valve	No
Valve design	Metal valve
Valve designation ETRTO	V5.01.1
Valve length [mm]	50.0
Valve angle [°]	gerade