

TYRES

Product group	Tyres
Item number	10001852
Valid tyre size	560 / 45 R 22.5
LI / SI / PR	160 D
TL/TT	TL
Brand	BKT
Tread pattern	FL 637



Notes and features

- The BKT FL637 is a radial flotation tyre for manure spreaders, agricultural trailers and tankers
- Its steel belts provide high loading capacities and long durability
- In the field, the tyre distinguishes itself with very good flotation characteristics, low rolling resistance and good self-cleaning properties
- The directional tread pattern provides excellent traction in field operations
- On the road, the tyre impresses with its good driving characteristics at speeds up to 65 km/h

Technical Informations

Item number	10001852
EAN	8903094074174
Valid tyre size	560 / 45 R 22.5
LI / SI / PR	160 D
TL/TT	TL
Brand	BKT
Tread pattern	FL 637
Carcass properties	Steel Belted
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 106
Nettogewicht [kg] (gültig)	105,72
Recommended rim size	AG16.00
Maximum air pressure [bar].	6,00
Section width (mm)	544
Outer diameter of tyre [mm].	1076
Stat. radius (SLR) [mm]	501
Speed Radius Index (SRI)	525
Rolling circumference [mm].	3324
Tread depth (mm)	21,5
Number of lugs	23x2
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
160 D	4500	65		6,00	