

TYRES

Product group	Tyres
Item number	10001858
Valid tyre size	205 / 75 R 17.5
LI / SI / PR	124 / 122 M, 14 PR
TL/TT	TL
Brand	Windpower
Tread pattern	PRO DR76





Technical Informations

Item number	10001858
EAN	4040658115325
Valid tyre size	205 / 75 R 17.5
LI / SI / PR	124 / 122 M, 14 PR
TL/TT	TL
Brand	Windpower
Tread pattern	PRO DR76
M+S	M+S
3PMSF	3PMSF
Axle position truck	RA
Rolling resistance	D

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.



Wet grip	С
Rolling noise [db].	71
Rolling noise level	A
Antistatic	No
Tyre colour	Black
ECE regulation number	ECE 54,ECE 117
Nettogewicht [kg] (gültig)	26,98
Recommended rim size	6.00
Permitted rim size	6.75, 7.50
Maximum air pressure [bar].	7,60
Section width (mm)	202
Tread width (mm)	180
Outer diameter of tyre [mm].	754
Rolling circumference [mm].	2300
Tread depth (mm)	14,0
E-Ready	No

Load capacity

Index	Load capacity [kg]	Speed [km/h]	Axle position	Inflation pressure [bar]	Load variant
124 M	1600	130	Single	7,60	
122 M	1500	130	Twin	7,60	

All information on these pages is based on the technical data of the manufacturers. The content is non-binding and is intended solely for information purposes. Bohnenkamp AG accepts no liability in connection with this data. Liability for any direct or indirect damages, claims for damages, consequential damages of any kind and on any legal grounds whatsoever arising from the use of the information obtained is excluded to the extent permitted by law.