

WHEELS

Product group	Wheels
Item number	10001870
Valid wheel size	6.5 / 80 - 12
Brand	BKT
Tread pattern	AS 504
Valid rim size	5 J x 12
Rim connection	6/161/205
Bolt hole design	B2
Offset (mm)	-5
Rim colour	Silver
Load capacity complete wheel [kg]	650
Speed complete wheel [km/h]	40



Technical Informations

Assembly Item no. Tyres	• 15711280
LI / SI / PR	80 A8 / 93 A8, 6 PR
Load capacity 1 [kg]	450
Speed 1 [km/h].	40
Load capacity 2 [kg]	650
Speed 2 [km/h].	40
Antistatic	No
Tyre colour	Black
Nettogewicht [kg] (gültig)	14,76
ECE regulation number	ECE 106
Section width (mm)	163

Stat. radius (SLR) [mm]	273
Rolling circumference [mm].	1851
Tread depth (mm)	14,5
Number of lugs	16x2
E-Ready	No
Assembly Item no. Rim	• 10001832
Load capacity of rim 1 [kg]	800
Speed Rims 1 [km/h]	40
Maximum speed [km/h].	40
Maximum air pressure [bar].	3,60
Type of drive	Towed axle
Hump	kein Hump
Valve protection	VS H
Single / multi-part	einteilig
Rim material	steel
RAL	RAL9006
Cavity Sealed	No
Disc thickness [mm]	10.0
Knurling	without knurling
Ventilation holes	No
Verschweißung beidseitig	No
Rim centering	BC
Number of bolt holes	6
Bolt hole design EUWA	B18 DS 32
Bolt hole diameter [mm]	21.5
Countersinking	Sphere
Spherical countersink [mm].	R16

hub hole diameter [mm].	161
Bolt hole circle diameter [mm]	205
Valve seat	External Valve
Valve hole diameter [mm]	11.3
Preassembled valve	No
Valve design	Rubber valve
Valve length [mm]	38
Valve angle [°]	gerade
Colour of cap	Black
Valve cap Material	Plastic